



MP15-MP16.5E

Since 1996 Marapco Generating Sets have provided reliable, dependable and trustworthy power solutions for the global market. Marapco Generating Sets combine quality and performance to deliver a superior product, making Marapco a market leading Generating Set throughout Nigeria.

Generator Output Rating at - 50Hz

380-415V	KVA	KW
Prime	15.0	12.0
Standby	16.5	13.2

@ 0.8 p.f.

Generator Output Rating at - 60Hz

480V	KVA	KW
Prime	NA	NA
Standby	NA	NA

@ 0.8 p.f.

Engine Data

Engine Manufacturer:	Perkins UK
Engine Model:	403A-15G2
Number of Cylinders:	3
Cylinder Arrangement:	Vertical In Line
Cycle:	4 Stroke
Bore/Stroke mm:	84 /90
Induction:	Naturally Aspirated
Compression ratio:	22.5:1
Displacement I (cu.in):	1.50 (91.0)

General Data

	Liter	US/Gal
Fuel Tank Capacity:	55.0	15.0
Fuel Tank:	Semi Bunded	
Base Frame:	Heavy Duty-Powder Painted	
Control Panel:	Deep Sea Electronics	
Circuit Breaker:	3 Pole/2 Pole MCB	

Performance

	50Hz		60Hz	
Engine Speed:	1500		1800	
Gross Engine Power:	<i>kWm</i>	<i>Bhp</i>	<i>kWm</i>	<i>Bhp</i>
<i>Prime:</i>	14.0	18.0	NA	NA
<i>Standby:</i>	15.0	20.0	NA	NA
Fuel Consumption:	<i>L/Hr</i>	<i>US Gal/Hr</i>	<i>L/Hr</i>	<i>US Gal/Hr</i>
<i>Prime:</i>	4.1	1.10	NA	NA
<i>Standby:</i>	4.9	1.30	NA	NA

Standard Reference Conditions:

Output ratings are presented at normal conditions of temperature and pressure. This generator set is designed to operate in high ambient temperatures and altitudes. Please consult your dealer for specific site ratings.

* In line with our policy of continuous product development, we reserve the right to change specification without notice.

Dimensions and Weights

Length		Width		Height		Dry		Wet	
Millimeter	Inch	Millimeter	Inch	Millimeter	Inch	KG	LB	KG	LB
1450.0	57.1	950.0	37.4	1110.0	43.7	452.0	996.5	460.0	1014.1

* With Lube Oil

* With Lube Oil & Coolant

10 F.K.GREEN STREET, OFF NTA ROAD, OZUOBA, NEW LAYOUT, PORT HARCOURT.

PHONE: 0700SPECOGREENO, 08099926124-8, 08037083181

Email: info@specogreeno.com.ng

Rating Definition

P Prime Rating

These rating are applicable for supplying continuous electrical power (at variable load) in lieu of commercially purchased power. This model can supply 10% overload power for 1 hour in 12 hours.

S Standby Rating

These rating are applicable for supply continuous electrical power (at variable load) in the event of utility power failure. *No overload is permitted on these ratings.* The alternator model is peak continuous rated (as defined in ISO 8528-3)

Air Flow

50 Hz 60 Hz

	M ³ /min		Ft ³ /min	
Combustion Air Flow:	1.10	39.0	NA	NA
Exhaust Gas Flow:	2.70	95	NA	NA
Radiator Cooling Air Flow:	-	-	NA	NA

*Cooling system designed to operate in ambient conditions

Alternator Data

Alternator Manufacturer:	Leroy Somer
Alternator Model:	LSA 40 S3
Number of Bearings:	Single (1)
Insulation Class:	H
Total Harmonic Content:	<3% on no load
Wires:	12
Ingress Protection Rating:	IP 23
Excitation System:	Shunt
Winding Pitch Code:	2/3 - 6

Principles



Perkins manufactures diesel engines and power solutions to the highest levels of performance and reliability. MARAPCO incorporates this engine throughout their full range.

Diesel Power



Leroy Somer is a world leader in the manufacturing of power generation, combining quality with performance to produce a market leading alternator for MARAPCO.



Deep Sea Electronics control modules deliver unrivaled functionality and performance. MARAPCO generating sets use this latest technology to its full potential.

Logos are registered trademarks of Perkins, Leroy Somer & Deep Sea Electronics

Sound Attenuated Enclosure

Length		Width		Height	
Millimeter	Inch	Millimeter	Inch	Millimeter	Inch
2000.0	78.8	950.0	37.4	1500.0	59.0

Sound Pressure Level's:	50 Hz	60 Hz
dBA @ 1m (100% Load)	79.0	N/A
dBA @ 5m (100% Load)	74.0	N/A
dBA @ 7m (100% Load)	69.0	N/A

*Please refer to the Sound Proof Brochure for more information

Cooling & Lubrication

50 Hz 60 Hz

	Liter		US/Gal	
Coolant Capacity:	6.0	1.6	NA	NA
Lube Oil Capacity:	6.0	1.6	NA	NA

	°C	°F	°C	°F
Exhaust Temperature:	470	878.0	NA	NA

Other Information

Generating Set Standards

This generating set meets the following standards: ISO8528, ISO3046

Warranty

This generator is covered against manufacturing and workmanship defects. Kindly refer to warranty statement for more details.

Picture shown in leaflet may include optional accessories

Distributed By:



10 F.K.GREEN STREET, OFF NTA ROAD, OZUOBA, NEW LAYOUT, PORT HARCOURT.

PHONE: 0700SPECOGREENO, 08099926124-8, 08037083181

Email: info@specogreeno.com.ng